

Telephone: +44 (0)113 259 1999

Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 01 April 2021

Our Ref: 23/58344-6 Your Ref: 2358066

Page: 1 of 4

Client: Silent Gliss Ltd

Pyramid Business Park

Poorhole Lane Broadstairs Kent CT10 2PT

Job Title: Surface Ignition Of Curtains & Drapes

Client's Order No: 2358066

Date of Receipt: 12 March 2021 Date of Test Start: 17 March 2021

Description of Sample(s): One sample identified as follows was received for testing:

Deep, Colour: 10, Version: Soft

Work Requested: We were asked to make the following test:

BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds







Telephone: +44 (0)113 259 1999 Email: <u>info@bttg.co.uk</u>

Website: www.bttg.co.uk

Date: 01 April 2021

Our Ref: 23/58344-6 Your Ref: 2358066

Page: 2 of 4

Silent Gliss Ltd

Sample was identified as follows:

Deep, Colour: 10, Version: Soft

<u>BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds Testing as received.</u>

Three specimens from both length and width were tested in accordance with BS EN ISO 15025: Procedure A (surface ignition): 2002. The sample was tested at 22°C and 38% relative humidity (R.H.).

Each specimen was subjected to an applied flame using propane and a 15 second flame application time. The results obtained (shown in the table below) were assessed according to the requirements of BS 5867: Part 2: 2008 (2015).

Pre-treatment

If the fabric is a <u>pass</u> in the `as received` condition, then the fabric is subjected a water soak procedure as specified in BS EN 1021: Annex D: 2006.

Testing after pre-treatment

Three specimens, after pre-treatment, from both length and width were tested following the procedure described above.

Test results relate only to the sample tested.

The results for all tests are given in the table(s) on the following page(s).

Reported by:.....

B Bland

Laboratory Technician

Countersigned By:.....

P Doherty

Manager

Enquiries concerning this report should be addressed to Customer Services.







Telephone: +44 (0)113 259 1999

Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 01 April 2021

Our Ref: 23/58344-6 Your Ref: 2358066

Page: 3 of 4

Silent Gliss Ltd

RESULTS

Sample Ref: Deep, Colour: 10, Version: Soft

BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds

Testing as Received

Specimen No.		Length			Width		
	1	2	3	4	5	6	
Flame reached an edge	No	No	No	No	No	No	
Hole reached an edge	No	No	No	No	No	No	
Flaming debris separated	No	No	No	No	No	No	

Requirements

Any "Yes" means fail except if only one specimen fails a further 6 specimens are tested, if the second 6 specimens all pass the result is a pass.

Result in `as received`: Pass

Testing after pre-treatment

	Length			Width		
Specimen No.	1	2	3	4	5	6
Flame reached an edge	No	No	No	No	No	No
Hole reached an edge	No	No	No	No	No	No
Flaming debris separated	No	No	No	No	No	No

Requirements

Any "Yes" means fail except if only one specimen fails a further 6 specimens are tested, if the second 6 specimens all pass the result is a pass.

Result in `after pre-treatment`: Pass





Telephone: +44 (0)113 259 1999

Email: <u>info@bttg.co.uk</u> Website: <u>www.bttg.co.uk</u>

Date: 01 April 2021

Our Ref: 23/58344-6 Your Ref: 2358066

Page: 4 of 4

Silent Gliss Ltd

Conclusion

The fabric meets the Type B performance requirements of BS 5867: Part 2: 2008 (2015).

This material should be identified with the manufacturers name, trademark or other identifying mark, the statement `Flammability complies with the requirements of BS 5867: Part 2: Type B and instructions of any special precautions to be taken concerning care (including cleansing) of the curtain, drape or window blind to be manufactured from the fabric, preferably using an appropriate care labelling symbol in accordance with BS EN 23758 and taking account of the pre-treatment using in this test and the requirements of Clause 4 of BS 5867: Part 2: 2008 (2015). If the fabric is unsuitable for cleansing, this shall be stated.

Uncertainty Budget

There is no uncertainty budget associated with BS 5867: Part 2: Type B as no measurements are determined, the pass/fail criteria is assessed visually.





Telephone: +44 (0)113 259 1999

Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 01 April 2021

Our Ref: 23/58344-5 Your Ref: 2358066

Page: 1 of 3

Client: Silent Gliss Ltd

Pyramid Business Park

Poorhole Lane Broadstairs Kent CT10 2PT

Job Title: Surface Ignition Of Curtains & Drapes (Type B)

Client's Order No: 2358066

Date of Receipt: 12 March 2021 Date of Test Start: 17 March 2021

Description of Sample(s): One sample of fabric identified as follows was received for testing:

Deep, Colour: 10, Version: Stiff

Work Requested: We were asked to make the following test:

BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds





Telephone: +44 (0)113 259 1999 Email: <u>info@bttg.co.uk</u>

Website: www.bttg.co.uk

Date: 01 April 2021

Our Ref: 23/58344-5 Your Ref: 2358066

Page: 2 of 3

Silent Gliss Ltd

Sample was identified as follows:

Deep, Colour: 10, Version: Stiff

BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds

Pre-treatment

None

Conditioning

The test specimens were conditioned for at least 24 hours in the standard atmosphere of 65 \pm 5 % relative humidity (R.H.) and 20 \pm 2 °C.

Testing

Three specimens from both length and width were tested in accordance with BS EN ISO 15025: Procedure A (surface ignition):2002.

Each specimen was subjected to an applied flame using propane and a 15 second flame application time. The results obtained (shown in the table below) were assessed according to the requirements of BS 5867: Part 2:2008 (2015).

Test results relate only to the sample tested.

The results for all tests are given in the table(s) on the following page(s).

Reported by B Bland

Laboratory Technician

Countersigned By:.....

P Doherty

Manager

Enquiries concerning this report should be addressed to Customer Services





Telephone: +44 (0)113 259 1999

Email: info@bttg.co.uk
Website: www.bttg.co.uk

Date: 01 April 2021

Our Ref: 23/58344-5 Your Ref: 2358066

Page: 3 of 3

Silent Gliss Ltd

RESULTS

Sample Ref: Deep, Colour: 10, Version: Stiff

BS 5867: Part 2: 2008 (2015): Type B Curtains, Drapes and Blinds

Testing as received.

	Length			Width			
Specimen No.	1	2	3	4	5	6	
Flame reached an edge	No	No	No	No	No	No	
Hole reached an edge	No	No	No	No	No	No	
Flaming debris separated	No	No	No	No	No	No	

Requirements

Any "Yes" means fail except if only one specimen fails a further 6 specimens are tested, it the second 6 specimens all pass the result is a pass.

Result: Pass

Conclusion

The fabric meets the Type B performance requirements of BS 5867: Part 2: 2008 – the fabric must be clearly labelled `If wetted in any way it is essential to re-treat the fabric to meet flammability requirements`.

The material should be identified with the manufacturers name, trademark or other identifying mark, the statement `Flammability complies with the requirements of BS 5867: Part 2, Type B and instructions of any special precautions to be taken concerning care (including cleansing) of the curtain, drape or window blind to be manufactured from the fabric, preferably using an appropriate care labelling symbol in accordance with BS EN 23758 and taking account of the pre-treatment used in this test and the requirements of Clause 4 of BS 5867: Part 2: 2008 (2011). If the fabric is unsuitable for cleansing, this shall be stated.

Note: This report relates only to the samples submitted and as described in the report.

Uncertainty Budget

There is no uncertainty budget associated with BS 5867: Part 2: Type B as no measurements are determined, the pass/fail criteria is assessed visually.



